

70mm Bright White PVCu Window ORDER/QUOTE FORM

Please tick for
quote only

PVC Direct Fax: 01453 826889 E-mail Orders: scheduler@customade.co.uk

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ Contact Numbers: _____

Please fax / e-mail confirmation to: _____

Please Circle Items Required

System: Feature / Bevel
Bead: Feature / Bevel / Special for 36mm TGU*
Outerframe: Slim (46mm) / Int (58mm) / Large (68mm)
Reinforcing: Steel / Thermal (where possible)
Glazed : Internal (welded) / External (mech)
Colour: Outside _____
 Inside _____
Energy Rating: A +* / A / B / C / None
Unit: 28mm DGU / 36mm* TGU (special bead)

Spacer Bar: Black / Grey / White
Glass Supply: Hourglass / Unglazed
Hinge Protection: None / SAC Bolt / GT Hinge Guard (For SBD)
SBD: Y / N **Doc Q:** Y / N **Glazing Clips:** Y (For SBD) / N
Handle Colour: White / Gold / Chrome / Black / Bronze
 Satin Silver / Graphite /
 Antique Black (Monkey tail)
Dummy Stay to side hung sashes: Y / N (Antique black only)
Lock: ERA VS1 / ERA Extreme VS3

(*Please refer to Information Bulletins or seek Technical Advice before selecting Triple glazing or A+ options)

Hinge abbreviations: S=Standard / E=Egress easy / R=Restrictor / RE=Restrictor Egress (TRI R90)

Location	Design (viewed outside, please show T/vents and mullion/trans dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge		Glass Spec (Tgh, Obs, Lead)	Add-ons 15 / 35		Special Requirements
			W	H		T/V			T	B	
					None 85 150 180 225	S E R RE			T B L R		
					None 85 150 180 225	S E R RE			T B L R		
					None 85 150 180 225	S E R RE			T B L R		
					None 85 150 180 225	S E R RE			T B L R		

WINDOW ORDER CONTINUATION SHEET

Order Ref:

Page of

Location	Design (viewed outside, please show T/vents and mullion/trans dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add-ons		Special Requirements
						T/V				
			W		None	S E		T		
					85	R RE		B		
			H		150	1250		L		
					180	2500		R		
					225					
			W		None	S		T		
					85	E R		B		
			H		150	1250		L		
					180	2500		R		
					225					
			W		None	S E		T		
					85	R RE		B		
			H		150	1250		L		
					180	2500		R		
					225					
			W		None	S E		T		
					85	R RE		B		
			H		150	1250		L		
					180	2500		R		
					225					
			W		None	S E		T		
					85	R RE		B		
			H		150	1250		L		
					180	2500		R		
					225					
			W		None	S E		T		
					85	R RE		B		
			H		150	1250		L		
					180	2500		R		
					225					