

70mm Bright White PVCu Window ORDER/QUOTE FORM

Please tick for
quote only

PVC Direct Fax: 01453 826889 E-mail Orders: scheduler@customade.co.uk

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ Contact Numbers: _____

Please fax / e-mail confirmation to: _____

Please Circle Items Required

System: Feature / Bevel
 Bead: Feature / Bevel / Special for 36mm TGU*
 Outerframe: Slim / Int / Large
 Reinforcing: Steel / Thermal (where possible)
 Glazed: Internal (welded) / External (mech)
 Colour: Outside _____
 Inside _____
 Energy Rating: A+* / A / B / C / None
 Unit: 28mm DGU / 36mm* TGU (special bead)

Spacer Bar: Black / Grey / White
 Glass Supply: Hourglass / Unglazed
 Stayguards: Y / N Glass Lock Clips: Y / N
 Handle Colour: White / Gold / Chrome
 Black / Satin Silver / Bronze
 Graphite / Antique Black (Monkey tail)
 Dummy Stay to side hung sashes: Y / N (Antique black only)
 (*Please refer to Information Bulletins or seek Technical Advice before selecting Triple glazing or A+ options)

Hinge abbreviations: S=Standard / E=Egress easy / R=Restrictor / RE=Restrictor Egress (TRI R90)

| Location | Design (viewed outside, please show T/vents and mullion/trans dimensions) | Qty | Sizes (mm) Including Cills & Add-ons | | Cill | Hinge | Glass Spec (Tgh, Obs, Lead) | Add-ons 15 / 35 | | Special Requirements |
|----------|---|-----|--------------------------------------|--|------|-------|-----------------------------|-----------------|---|----------------------|
| | | | | | | T/V | | T | B | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |

WINDOW ORDER CONTINUATION SHEET

Order Ref:

Page of

| Location | Design (viewed outside, please show T/vents and mullion/trans dimensions) | Qty | Sizes (mm) Including Cills & Add-ons | | Cill | Hinge | Glass Spec (Tgh, Obs, Lead) | Add-ons | | Special Requirements |
|----------|---|-----|--------------------------------------|--|------|-------|-----------------------------|---------|--|----------------------|
| | | | | | | T/V | | | | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |
| | | | W | | None | S | | T | | |
| | | | | | 85 | E R | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |
| | | | W | | None | S E | | T | | |
| | | | | | 85 | R RE | | B | | |
| | | | H | | 150 | 1250 | | L | | |
| | | | | | 180 | 2500 | | R | | |