

White/Foil PVCu Window ORDER FORM

Please tick for
quote only

Page: _____
of: _____

Company Name (Acc No): _____

Please email/fax confirmation to: _____

Contact Name: _____

Order Ref/No: _____

Contact Numbers: _____

Preferred Delivery Date: _____

Please Circle Items Required

System:	Sculptured / Chamfered	Energy Rating:	A / B / C / None
Outerframe:	Standard 55mm / Large 75mm	Unit:	28mm DGU / 36mm Triple-Glazed Unit (Chamfered)
Reinforcing: <i>(Where possible)</i>	Steel / Full Steel Reinforcing / Thermal	Warm Edge Spacer:	Black / Grey / White
Colour:	White / Rosewood / Golden Oak / Rosewood on White / Golden Oak on White / Cream / Black on White / Anthracite Grey on White	Glass Supply:	Unglazed / Glazed / Loose glass
Special Colours:	Out: _____ In: _____	Lock Type:	Espag / Shootbolt / Central Locking Shootbolt
Handle Colour:	White / Gold / Chrome / Black / Satin Silver	Hinge Guards:	Y / N
Bead:	Sculptured / Chamfered / Special for 36mm Triple-Glazed Unit* (Chamfered)	Glass Clips:	Y / N
Trickle Vent	Frame / Sash	Upgrade Required*?	<input type="checkbox"/> SBD <input type="checkbox"/> Document Q <input type="checkbox"/> PAS24 <input type="checkbox"/> Polyframe Protection Promise

Special colours are on a longer lead time. Please check with your sales order processing team for details.

*SBD/PAS24/Doc.Q Shootbolt Lock, Stayguards & Glass Clips
*Polyframe Protection Promise Shootbolt Lock, Stayguards & Glass Clips

Hinge abbreviations: S=Standard / E=Egress easy / R=Restrictor

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Cill	Hinge	Glass Spec (Tough, Obs, Lead)	Add-ons 15mm/25mm/50mm Couplers 2mm/10mm/20mm		Special Requirements
		Width	Height		T/V		T	B	
				None 85 150 180 225	S E R		T B L		
Location:		Mullion		Concealed Face Drain	2500		R		
				None 85 150 180 225	S E R		T B L		
Location:		Mullion		Concealed Face Drain	2500		R		
				None 85 150 180 225	S E R		T B L		
Location:		Mullion		Concealed Face Drain	2500		R		
				None 85 150 180 225	S E R		T B L		
Location:		Mullion		Concealed Face Drain	2500		R		

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated.

Signature: _____

Date: _____



BS7412/PAS24
KM45766



License No: FM663279



BS7412
KM45620



E-mail Orders: sales@polyframetrade.co.uk

PVC Direct Fax: 01422 383292

Standard Terms and Conditions Apply

White/Foil PVCu Window ORDER/QUOTE FORM - Continuation Sheet

Order Page: _____
Ref: _____ of: _____

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Cill	Hinge	Glass Spec (Tough, Obs, Lead)	Add-ons		Special Requirements
					T/V		15mm/25mm/50mm Couplers 2mm/10mm/20mm		
		Width		None 85 150 180 225	S E R		T		
		Height					1250	B	
		Transom			2500			L	
Location:		Mullion					Concealed Face Drain	R	
		Width		None 85 150 180 225	S E R		T		
		Height					1250	B	
		Transom			2500			L	
Location:		Mullion					Concealed Face Drain	R	
		Width		None 85 150 180 225	S E R		T		
		Height					1250	B	
		Transom			2500			L	
Location:		Mullion					Concealed Face Drain	R	
		Width		None 85 150 180 225	S E R		T		
		Height					1250	B	
		Transom			2500			L	
Location:		Mullion					Concealed Face Drain	R	
		Width		None 85 150 180 225	S E R		T		
		Height					1250	B	
		Transom			2500			L	
Location:		Mullion					Concealed Face Drain	R	
		Width		None 85 150 180 225	S E R		T		
		Height					1250	B	
		Transom			2500			L	
Location:		Mullion					Concealed Face Drain	R	
		Width		None 85 150 180 225	S E R		T		
		Height					1250	B	
		Transom			2500			L	
Location:		Mullion					Concealed Face Drain	R	
		Width		None 85 150 180 225	S E R		T		
		Height					1250	B	
		Transom			2500			L	
Location:		Mullion					Concealed Face Drain	R	

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated.

Signature: _____

Date: _____

