



White/Foil PVCu Door ORDER FORM

Please tick for
quote only

Page: _____
of: _____

Company Name (Acc No): _____

Please email/fax confirmation to: _____

Contact Name: _____

Order Ref/No: _____

Contact Numbers: _____

Preferred Delivery Date: _____

Please Circle Items Required

System:	Sculptured / Chamfered	Energy Rating:	A / B / C / None
Reinforcing: <i>(Where possible)</i>	Steel / Full Steel Reinforcing / Thermal (where possible)	Unit:	28mm DGU / 36mm Triple-Glazed Unit (Chamfered)
Colour:	White / Rosewood / Golden Oak / Rosewood on White / Golden Oak on White / Cream / Black on White / Anthracite Grey on White	Warm Edge Spacer:	Black / Grey / White
Special Colours:	Out: _____ In: _____	Glass Supply:	Unglazed / Glazed / Loose glass
Hardware Colour:	White / Gold / Chrome / Black / Satin Silver	Lock Type:	4 Roller (Standard) / 3 Hook & 2 Roller / 3 Hook & 2 Roller & Shootbolt
Hinge Colour	White / Gold / Chrome / Black / Satin Silver / Light Oak / Brown / Anthracite Grey / Cream	Cylinder:	6 Pin / 1* Cylinder / 1* Cylinder & Guard / 3* Cylinder
Bead:	Sculptured / Chamfered / Special for 36mm Triple-Glazed Unit* (Chamfered)	Hinge Guards:	Y / N Cylinder Guard: Y / N
Trickle Vent position:	Frame / Sash	Glass Clips:	Y / N
		Upgrade Required*?	<input type="checkbox"/> SBD <input type="checkbox"/> Document Q <input type="checkbox"/> PAS24 <input type="checkbox"/> Polyframe Protection Promise
Special colours are on a longer lead time. Please check with your sales order processing team for details.		*SBD/PAS24/Doc.Q	3 Hook & 2 Roller, Hinge Guards, Glass Clips & 1* Cylinder and guard or 3* Cylinder
		Polyframe Protection Promise	3 Hook & 2 Roller, Hinge Guards, Glass Clips & 1 Cylinder with Guard or 3* Cylinder

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Add-ons 15mm/30mm/50mm Couplers 2mm/6mm/20mm		Special Requirements (inc letterplate colour etc)
<i>Show Hinge Side & Master Door (M)</i>		Width	Cill	None / 85 / 150 / 180	T	
		Height	Handle	Lever-Lever / Lever-Pad / Panic Bar	B	
		Transom	Open	In Out Restrictor on open out <input type="checkbox"/>	L	
		Mullion	Trickle Vent	1250 / 2500	R	
Location:		Threshold		PVCu 72mm / PVCu 56mm / Ali 44mm / Ali 15mm		
		Width	Cill	None / 85 / 150 / 180	T	
		Height	Handle	Lever-Lever / Lever-Pad / Panic Bar	B	
		Transom	Open	In Out Restrictor on open out <input type="checkbox"/>	L	
		Mullion	Trickle Vent	1250 / 2500	R	
Location:		Threshold		PVCu 72mm / PVCu 56mm / Ali 44mm / Ali 15mm		
		Width	Cill	None / 85 / 150 / 180	T	
		Height	Handle	Lever-Lever / Lever-Pad / Panic Bar	B	
		Transom	Open	In Out Restrictor on open out <input type="checkbox"/>	L	
		Mullion	Trickle Vent	1250 / 2500	R	
Location:		Threshold		PVCu 72mm / PVCu 56mm / Ali 44mm / Ali 15mm		

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated. Weather rating is not guaranteed on a 15mm aluminium threshold.

Signature: _____

Date: _____



BS7412/PAS24
KM649306

License No: FM663297

Police Preferred Specification



White/Foil PVCu Door ORDER/QUOTE FORM - Continuation Sheet

Order Ref: _____ Page: _____ of: _____

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Add-ons 15mm/30mm/50mm Couplers 2mm/6mm/20mm		Special Requirements (inc letterplate colour etc)
<i>Show Hinge Side & Master Door (M)</i>		Width	Cill	None / 85 / 150 / 180	T	
		Height	Handle	Lever-Lever / Lever-Pad / Panic Bar	B	
		Transom	Open	In Out Restrictor on open out <input type="checkbox"/>	L	
		Mullion	Trickle Vent	1250 / 2500	R	
Location:			Threshold	PVCu 72mm / PVCu 56mm / Ali 44mm / Ali 15mm		
		Width	Cill	None / 85 / 150 / 180	T	
		Height	Handle	Lever-Lever / Lever-Pad / Panic Bar	B	
		Transom	Open	In Out Restrictor on open out <input type="checkbox"/>	L	
		Mullion	Trickle Vent	1250 / 2500	R	
Location:			Threshold	PVCu 72mm / PVCu 56mm / Ali 44mm / Ali 15mm		
		Width	Cill	None / 85 / 150 / 180	T	
		Height	Handle	Lever-Lever / Lever-Pad / Panic Bar	B	
		Transom	Open	In Out Restrictor on open out <input type="checkbox"/>	L	
		Mullion	Trickle Vent	1250 / 2500	R	
Location:			Threshold	PVCu 72mm / PVCu 56mm / Ali 44mm / Ali 15mm		
		Width	Cill	None / 85 / 150 / 180	T	
		Height	Handle	Lever-Lever / Lever-Pad / Panic Bar	B	
		Transom	Open	In Out Restrictor on open out <input type="checkbox"/>	L	
		Mullion	Trickle Vent	1250 / 2500	R	
Location:			Threshold	PVCu 72mm / PVCu 56mm / Ali 44mm / Ali 15mm		
		Width	Cill	None / 85 / 150 / 180	T	
		Height	Handle	Lever-Lever / Lever-Pad / Panic Bar	B	
		Transom	Open	In Out Restrictor on open out <input type="checkbox"/>	L	
		Mullion	Trickle Vent	1250 / 2500	R	
Location:			Threshold	PVCu 72mm / PVCu 56mm / Ali 44mm / Ali 15mm		

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated. Weather rating is not guaranteed on a 15mm aluminium threshold.

Signature: _____

Date: _____

E-mail Orders: sales@polyframetrade.co.uk
Standard Terms and Conditions Apply

PVC Direct Fax: 01422 383292



BS7412/PAS24
KM649306



License No: FM663297

