



White/Foil PVCu Window ORDER FORM

Please tick for quote only

Page: _____
 of: _____

Company Name (Acc No): _____

Please email/fax confirmation to: _____

Contact Name: _____

Order Ref/No: _____

Contact Numbers: _____

Preferred Delivery Date: _____

Please Circle Items Required

System:	Sculptured / Chamfered	Energy Rating:	A+ / A / B / C / None
Outerframe:	Standard 56mm / Large 72mm	Unit:	28mm DGU / 36mm Triple-Glazed Unit (Chamfered)
Reinforcing:	Steel / Full Steel Reinforcing / Thermal (where possible)	Warm Edge Spacer:	Black / Grey / White
Colour:	White / Rosewood / Golden Oak / Rosewood on White / Golden Oak on White / Cream / Black on White / Anthracite Grey on White	Glass Supply:	Unglazed / Glazed / Loose glass
Special Colours*:	Out: _____ In: _____	Lock Type:	Espag / Shootbolt / Central Locking Shootbolt
Handle Colour:	White / Gold / Chrome / Black / Satin Silver	Hinge Guards:	Y / N
Bead:	Sculptured / Chamfered / Special for 36mm Triple-Glazed Unit* (Chamfered)	Glass Clips:	Y / N
Trickle Vent	Frame / Sash	Upgrade Required*	<input type="checkbox"/> SBD <input type="checkbox"/> Document Q <input type="checkbox"/> PAS24 <input type="checkbox"/> Polyframe Protection Promise

Special colours are on a longer lead time. Please check with your sales order processing team for details.

*SBD/PAS24/Doc.Q Shootbolt Lock, Hinge Guards & Glass Clips
 *Polyframe Protection Promise Shootbolt Lock, Hinge Guards & Glass Clips

Hinge abbreviations: S=Standard / E=Egress easy / R=Restrictor

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Cill	Hinge	Glass Spec (Tough, Obs, Lead)	Add-ons 15mm/30mm/50mm Couplers 2mm/6mm/20mm		Special Requirements
		Width	Height		T/V		T	B	
				None 85 150 180	S E R		T B L		
Location:		Mullion		Concealed Face Drain	2500		R		
				None 85 150 180	S E R		T B L		
Location:		Mullion		Concealed Face Drain	2500		R		
				None 85 150 180	S E R		T B L		
Location:		Mullion		Concealed Face Drain	2500		R		
				None 85 150 180	S E R		T B L		
Location:		Mullion		Concealed Face Drain	2500		R		

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated.

Signature: _____

Date: _____



BS7412/PAS24
KM649306



License No: FM663297



Police Preferred Specification

E-mail Orders: sales@polyframetrade.co.uk

PVC Direct Fax: 01422 383292

Standard Terms and Conditions Apply



White/Foil PVCu Window ORDER/QUOTE FORM - Continuation Sheet

Order Ref: _____ Page: _____ of: _____

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Cill	Hinge	Glass Spec (Tough, Obs, Lead)	Add-ons 15mm/30mm/50mm Couplers 2mm/6mm/20mm		Special Requirements	
		Width	Height		T/V		T	B		
		Width		None 85 150 180	S E R		T			
		Height					1250	L		
		Transom					2500	R		
Location:		Mullion		Concealed Face Drain	2500					
		Width		None 85 150 180	S E R		T			
		Height					1250	L		
		Transom					2500	R		
Location:		Mullion		Concealed Face Drain	2500					
		Width		None 85 150 180	S E R		T			
		Height					1250	L		
		Transom					2500	R		
Location:		Mullion		Concealed Face Drain	2500					
		Width		None 85 150 180	S E R		T			
		Height					1250	L		
		Transom					2500	R		
Location:		Mullion		Concealed Face Drain	2500					
		Width		None 85 150 180	S E R		T			
		Height					1250	L		
		Transom					2500	R		
Location:		Mullion		Concealed Face Drain	2500					
		Width		None 85 150 180	S E R		T			
		Height					1250	L		
		Transom					2500	R		
Location:		Mullion		Concealed Face Drain	2500					
		Width		None 85 150 180	S E R		T			
		Height					1250	L		
		Transom					2500	R		
Location:		Mullion		Concealed Face Drain	2500					
		Width		None 85 150 180	S E R		T			
		Height					1250	L		
		Transom					2500	R		
Location:		Mullion		Concealed Face Drain	2500					

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated.

Signature: _____

Date: _____

E-mail Orders: sales@polyframetrade.co.uk

PVC Direct Fax: 01422 383292

Standard Terms and Conditions Apply



BS7412/PAS24
KM649306



License No: FM663297



Police Preferred Specification