

White/Foil PVCu Window ORDER FORM

Please tick for quote only

Page: _____
 of: _____

Company Name (Acc No): _____

Please email/fax confirmation to: _____

Contact Name: _____

Order Ref/No: _____

Contact Numbers: _____

Preferred Delivery Date: _____

Please Circle Items Required			
System:	Sculptured / Chamfered	Energy Rating:	A+ / A / B / C / None
Outerframe:	Standard 52mm / Medium 62mm / Large 72mm	Unit:	28mm DGU / 36mm Triple-Glazed Unit (Chamfered)
Reinforcing:	Steel / Full Steel Reinforcing	Warm Edge Spacer:	Black / Grey / White
Colour:	White / Rosewood / Golden Oak / Mahogany (C) / Rosewood on White / Golden Oak on White / Mahogany on White (C) / Smooth Anth Grey on White (C) / Black on White (S) / White Grain (S) / Anth Grey on White (S) / Cream Grain (S)	Glass Supply:	Unglazed / Glazed / Loose Glass
Special Colours*:	Out: _____ In: _____ (sprayed)	Lock Type:	Espag / Shootbolt / Central Locking Shootbolt / Rapide
Handle Colour:	White / Gold / Chrome / Black / Satin Silver	Stayguards:	Y / N
Bead:	Sculptured / Chamfered / Special for 36mm Triple-Glazed Unit* (Chamfered)	Glass Clips:	Y / N
Trickle Vent position:	Frame / Sash	Upgrade Required*?	<input type="checkbox"/> SBD <input type="checkbox"/> Document Q <input type="checkbox"/> PAS24 <input type="checkbox"/> Polyframe Protection Promise
<small>Special colours are on a longer lead time. Please check with your sales order processing team for details.</small>		<small>*SBD/PAS24/Doc.Q Shootbolt Lock, Hinge Guards & Glass Clips *Polyframe Protection Promise Shootbolt Lock & Hinge Guards & Glass Clips</small>	

Hinge abbreviations: **S**=Standard / **E**=Egress easy / **R**=Restrictor

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Cill	Hinge	Glass Spec (Tough, Obs, Lead)	Add-ons 15mm/45mm Couplers 3mm/7.5mm/20mm	Special Requirements
		Width	Height		T/V			
		Width		None 95 150 180 225	S E R		T	
		Height					B	
		Transom			1250		L	
Location:		Mullion		Concealed Face Drain	2500		R	
		Width		None 95 150 180 225	S E R		T	
		Height					B	
		Transom			1250		L	
Location:		Mullion		Concealed Face Drain	2500		R	
		Width		None 95 150 180 225	S E R		T	
		Height					B	
		Transom			1250		L	
Location:		Mullion		Concealed Face Drain	2500		R	
		Width		None 95 150 180 225	S E R		T	
		Height					B	
		Transom			1250		L	
Location:		Mullion		Concealed Face Drain	2500		R	

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated.

Signature: _____

Date: _____



BS7412/PAS24
KM647570



BS7412
KM647569



Police Preferred Specification

White/Foil PVCu Window ORDER/QUOTE FORM - Continuation Sheet

Order Ref: _____ Page: _____
 of: _____

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Cill	Hinge	Glass Spec (Tough, Obs, Lead)	Add-ons 15/45		Special Requirements
					T/V				
		Width		None 95 150 180 225	S E R		T		
		Height							
		Transom			2500		L		
Location:		Mullion							
		Width		None 95 150 180 225	S E R		T		
		Height							
		Transom			2500		L		
Location:		Mullion							
		Width		None 95 150 180 225	S E R		T		
		Height							
		Transom			2500		L		
Location:		Mullion							
		Width		None 95 150 180 225	S E R		T		
		Height							
		Transom			2500		L		
Location:		Mullion							
		Width		None 95 150 180 225	S E R		T		
		Height							
		Transom			2500		L		
Location:		Mullion							
		Width		None 95 150 180 225	S E R		T		
		Height							
		Transom			2500		L		
Location:		Mullion							
		Width		None 95 150 180 225	S E R		T		
		Height							
		Transom			2500		L		
Location:		Mullion							
		Width		None 95 150 180 225	S E R		T		
		Height							
		Transom			2500		L		
Location:		Mullion							

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated.

Signature: _____

Date: _____



E-mail Orders: sales@polyframenorwich.co.uk
 Standard Terms and Conditions Apply

PVC Direct Fax: 01603 308161