Polyframe Atlas Works, Norwich Road, Lenwade, Norwich, NR₉ ₅SR, Tel:01603 879581





Window ORDER / QUOTE FORM

Email Orders/Quotes to commercial.ops@polyframenorwich.co.uk					Please tick for Page: quote only of:							
Company Name (Acc No):					Please email/fax confirmation to:							
Contact Name:						_						
Contact Numbers:												
Please Circle Items												
System: Chamfered 7oC / Sculptured 7oS Bead Type: Ovolo / Flat									e fixed			
Window	Casement / Flush Sash / Tilt and Turn (TBT) / Fully Reversible					le (FR)	Handle:		Standard Monkey			
Outerframe:	Small 52mm / Medium 62mm / Large 72mm / (FR) 62mm						Handle Colour:		(Monkey tail only available in White Black Gold			
Reinforcing:	Standard / Fully Reinforced						Casements:					
Colours:	External Colour: Choices: External Colour:			Choices:	Monkey Tail:		White Black Pewi					
	White		70C&70S	Pearl Grey**		70C	WERS:		A or U value required WER'S and U values are not ap	oplicable if unglazed		
	Golden Oak*		70C&70S	Chartwell Greer	1*	70C&70S	Glass Supply:		DGU unglazed / TGU ur	nglazed / Glazed / Loose glass		
	Rosewood*		70C&70S	Slate Grey smoo	oth*	70C	Unit thickness:		28mm DGU / 36mm TGU / 44mm TGU			
	Anthracite Grey Sn	nooth*	70C	White Woodgra		70S	Specified glass:		Not available in Flush sash Georgian Bar Astragal Bar Lead			
	Anthracite Grey gra	ained*	70C&70S	Clotted Cream *	ŧ	70S			(Astragal bar not available in flush sash 36mm TGU)			
	Irish oak*		70C	Black*		70S	Lock Type:			Yale Shootbolt (L1)		
	Mahogany*		70C							1) / Yale Rapide (L2)		
Key:	* foils are available b			ace only	Internal Co		Hinge Guards:		Y / N			
	** foils are available on e *** foils are available bot		•	Foil both si White	PAS24 Upgrade:		:	No / PPP Level 1 / PPP Level 2 (PPP Level 1 (L1) uses Yale shootbolts and Level 2 (L2) uses the Yale				
				th grey both sides and on white, Irish oak both sides and or					Rapide, both meet PAS24.)			
Mahogany both side			and on white, Pearl grey on white, Slate grey smooth both s lable in the 7oC chamfered casement suite.						None / Yale / Glazpart			
	White grain both side sides and on white, a	es and C	lotted cream both	sides and on white		wn both	TV Position:		Frame / Sash / Note - TV not available in 52m			
	Hinge abbreviat	ions: S	s: S=Standard / E=Egress easy / R=Restrictor /CR=				trictor (CR only used)	with st	tandard and egress easy cle	an hinges)		
Design (viewed outside, please show trickle		Qty	Sizes (mm)		Cill Size	Hinge	Glass Spec (Tough, Lam, Obs,	1	d-ons 15mm / 45mm Couplers Special Requirements			
vents & mullion/tra			Including cill	s & add-ons	Drainage	TV mm2	Lead)		gmm / 7.5mm / 24mm			
			Width		None	S		Т				
					95 150	E R		\vdash				
			Height		180 225	- CR		В				
			Transom			2500		L				
			Mullion		Concealed Face Drain	4000 5000		R				
Location:			Width		None 95	S		Т				
						E R						
			Height		180 225	- CR		В				
			Transom		Concealed	2500 4000 5000		L				
			Mullion		Face Drain			R				
All units viewed externally, cills and add-ons included in overall dimensions. All products are inte					_ - i=+	anlamad suct are act						

Please refer to the Polyframe Rehau Foil Colour Range information sheets for lead times, as some of the foils may be on extended lead times.

Signature:
Date:
E-mail Orders: commercial.ops@polyframenorwich.co.uk
Standard Terms and Conditions Apply



Window ORDER/QUOTE FORM - Continuation Sheet



Order	Page:
Ref:	of:

Design (viewed outside, please show trickle vents & mullion/transom dimensions)	Qty	Sizes (mm) Including cills & add-ons		Cill	Hinge TV mm2	Glass Spec (Tough, Lam, Obs, Lead)		Add-ons 15mm/45mm Couplers 3mm / 7.5mm / 24mm	Special Requirements
		Width		None 95 150 180 225	S E R - CR 2500 4000 5000		т		
		Height					В		
		Transom		Concealed Face Drain			L		
Location:		Mullion					R		
		Width		None 95 150 180 225	S E R - CR		т		
		Height					В		
		Transom		Concealed Face Drain	2500 4000 5000		L		
Location:		Mullion					R		
		Width		None 95 150 180 225	S E R - CR - 2500 4000 5000		т		
		Height					В		
		Transom		Concealed Face Drain			L		
Location:		Mullion					R		
		Width		None 95 150 180 225	S E R -		т		
		Height					В		
		Transom		Concealed	2500 4000		L		
Location:		Mullion		Face Drain	5000		R		
		Width		None 95 150 180 225	S E R -		т		
		Height					В	В	
		Transom		Concealed Face Drain	2500 4000 5000		L		
Location:		Mullion					R		

All units viewed externally, cills and add-ons included in overall dimensions. All products are internally glazed unless otherwise stated. Please refer to the Polyframe Rehau Foil Colour Range information sheets for lead times, as some of the foils may be on extended lead times.

Signature:
Date:
E-mail Orders: commercial.ops@polyframenorwich.co.uk Standard Terms and Conditions Apply

